



# RED LINE 75W140 GL-5 GEAR OIL



- Popular for cars and light trucks like Ford Mustang, Ford F-150, Dodge Ram, Toyota Tundra and Sequoia, and Jeep Cherokee
- Contains additional friction modifiers for suitability with clutch-type limited slip differentials - for most LSDs, no additional friction modifiers are required
- This product is not designed for use in most manual transmissions or tranaxles, since the extreme slipperiness may cause synchronizer mesh issues that lead to shifting problems

## RECOMMENDED FOR:

API GL-5 and MT-1  
MIL-L-2105E  
SAE J2360

### Dodge

2003-2006 Ram Pickup  
2003-2004 Dakota, Durango with trailer towing package  
2005-2009 Dakota, Durango, Aspen rear differential  
2008-2009 1500, 2500, 3500 C200FE front diffs, all corporate rear axles

### BMW

2002-present with Ltd Slip (M series)

### Chevrolet/GMC

1993-2000 3500HD with Dana 80

### Ford

2001- 2004 Mustang Cobra  
2002-present Mustangs  
2002-2006 Lincoln LS  
1999-2006 Lincoln LS (Sport)  
1998-2000 5-liter Explorer  
1998-present Explorer, Expedition, F-150, E250, E-350  
1999-2004 F-250  
1998-2006 E-150

### Nissan

'04-Frontier, XTerra M226 rear dif  
2004-2008 Titan rear dif

### Jeep

1993- 2007 Cherokee, Grand Cherokee, Grand Wagoneer, Wrangler Class III or Class IV hitch, towing package Grand Cherokee w/Vari-Lock or Quadra Drive  
2008-present Commander and Grand Cherokee all differentials  
2005-2006 Rubicon with 226 rear dif

2002-2003 Liberty Front and '02 - '07 198RBI rear dif, '08 - 8 1/4" rear differential  
2007-present Nitro 8 1/4"

### Jaguar

2000-present S-Type, X-Type  
2007-XK series  
2004-2007 XJ8, XJR  
2008-present All Vehicles

### Toyota

2004-present Tundra w/o Ltd Slip  
2002 on Sequoia

## TYPICAL PROPERTIES:

API Service Class	GL 5+
SAE Viscosity Grade (Gear Oil)	75W140
Vis @ 100°C, cSt	27.8
Vis @ 40°C, cSt	192
Viscosity Index	183
Pour Point, °C	-45
Pour Point, °F	-49
Brookfield Viscosity, Poise	1300 @-40°C

## PACKAGE SIZES:

57914 - 75W140 GL-5 Gear Oil - quart  
57915 - 75W140 GL-5 Gear Oil - gallon  
57916 - 75W140 GL-5 Gear Oil - 5 gallon  
57917 - 75W140 GL-5 Gear Oil - 16 gallon  
57918 - 75W140 GL-5 Gear Oil - 55 gallon

## ABOUT RED LINE GEAR OIL FOR DIFFERENTIALS

- Fully-synthetic formulas created from polyol ester base stocks, offer excellent lubrication under extreme conditions
- High viscosity-index (VI) to provide relatively constant viscosity and film thickness with varying temperature change
- Ester base stocks and friction modifiers provide additional slipperiness to lower operating temperatures by reducing the sliding friction in hypoid gears
- Superior shear stability and reduced oxidation compared to other synthetics and conventional gear oils
- Exceed API GL-5 specifications
- Engineered to provide the highest degree of protection and improvement of differential efficiency for better mileage, longer drain intervals, and less wear

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM