



RED LINE HIGH-TEMP ATF



- For heavily-loaded vehicles, allowing operation at up to 70°F higher while maintaining thicker viscosity than traditional ATFs
- Use where Dexron III®, Dexron II®, Mercon®, or GL-4 gear oil are recommended
- Dramatically less evaporation, less varnish of valves and clutches in extreme conditions

RECOMMENDED FOR:

DEXRON® II/III

FORD MERCON®/MERCON V

TOWING, RV, AND TRUCK APPLICATIONS

Dexron and Mercon are trademarks owned by General Motors and Ford Motor Co., respectively.

TYPICAL PROPERTIES:

Vis @ 100°C, cSt	10
Vis @ 40°C, cSt	53.9
Viscosity Index	172
Pour Point, °C	-51
Pour Point, °F	-60
Brookfield Vis @ -40°C, P	175

PACKAGE SIZES:

- 30204 - High-Temp ATF - quart
- 30205 - High-Temp ATF - gallon
- 30206 - High-Temp ATF - 5 gallon
- 30207 - High-Temp ATF - 16 gallon

ABOUT RED LINE AUTOMATIC TRANSMISSION FLUIDS

- Red Line offers the widest selection of fully-synthetic ATF on the market today
- Each offer improved thermal stability, maintain viscosity levels, and feature lower volatility while providing the required frictional characteristics of each fluid's OEM-style replacement
- Reduced oxidation and lower volatility at high temperature
- Allows high-temp operation without varnishing valves and clutches
- Extended drain intervals

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM